

CLEAN MASTER™ PRESSURE WASH - 1 WB

FORMERLY POWERCLEAN



-size	↔		↕		⌚		🔥		👤		📦	⚖️	🗑️
	DN	"	"	mm	PSI	MPa	PSI	MPa	mm	m	kg/100m	REF.	
-4	6	1/4	0,52	13,2	4000	28,0	12000	84,0	50	91	24	CLEAN MAS 4PW4000	
-5	8	5/16	0,59	14,9	4000	28,0	12000	84,0	55	91	27	CLEAN MAS 5PW4000	
-6	10	3/8	0,66	16,8	4000	28,0	12000	84,0	65	91	34	CLEAN MAS 6PW4000	
-5	8	5/16	0,59	14,9	4000	28,0	12000	84,0	55	91	27	CLEAN MAS 5PW4000B	
-6	10	3/8	0,66	16,8	4000	28,0	12000	84,0	65	91	34	CLEAN MAS 6PW4000B	
-8	12	1/2	0,78	19,8	3000	21,0	9000	62,0	90	91	43	CLEAN MAS 8PW3000B	
-6	10	3/8	0,66	16,8	4000	28,0	12000	84,0	65	91	34	CLEAN MAS 6PW4000G	
-8	12	1/2	0,78	19,8	3000	21,0	9000	62,0	90	91	43	CLEAN MAS 8PW3000G	

RECOMMENDED FOR

Use on pressure cleaning equipment for commercial and industrial purposes, in food processing, sanitation and car wash applications. All hot and cold water high-pressure cleaning services.

TUBE

NBR (Nitrile) based. Black.

REINFORCEMENT

One braid of high tensile steel wire

COVER

Modified Nitrile. MSHA approved. Available in black, blue (B) and grey (G). Blue and grey covers are non-marking.

TEMPERATURE RANGE

-40°C to +121°C and +150°C intermittent (to EN 1829-2). For water emulsions, etc. see Temperature Limits Table.

STANDARDS

Exceeds EN 1829-2.

COUPLINGS

MegaCrimp®.

CHARACTERISTICS/BENEFITS

Abrasion and ozone resistant cover.

IMPORTANT

Not for steam service.