

Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	03/08/2018
Datasheet No:	DS1098W
Parker Part No:	938348Q
OEM:	MP Filtri
OEM Part No:	HP1352A25VN&AN

Product Dimensions

A (mm)	53.0	(inch)	2.09
B (mm)	27.5	(inch)	1.08
D (mm)	53	(inch)	2.09
E (mm)	229.0	(inch)	9.02



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Mild steel tin plated
Bottom Endcap:	Mild steel tin plated
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	0.29 bar @ 200 l/min
Tested to ISO3968 @ 32 cSt	4.21 psi @ 43.99 gpm
Efficiency:	>Beta 200 @ 20 microns & greater >Beta 1000 @ 22 microns & greater
Minimum Collapse Pressure:	>20 bar
Tested to ISO2941	>290 psi
Dirt Holding Capacity acc. to ISO16889	>24.6 gram @ 7 bar terminal pressure drop >24.6 gram @ 102 psi terminal pressure drop