



Acqua fredda
Cold water



Per uso professionale
For professional usage



Accessori professionali
Professional accessories

TSS[®]
Total Stop
SYSTEM



ø 30 cm

Caratteristiche Generali - General Features:

- Carrello robusto in metallo a due ruote completo di manico
- Pompa a 3 pistoni in ceramica, con sistema biella-manovella
- Testa pompa in ottone
- Valvola di by-pass automatica con azzeramento della pressione nella testa della pompa
- Sistema di arresto totale dell' idropulitrice a distanza
- Motore elettrico a induzione trifase con protezione termica
- Valvola di regolazione flangiata (VRZ)
- Manometro
- Aspirazione detergente incorporata
- Aspirazione detergente regolabile
- Capacità del serbatoio detergente 3 l
- Filtro acqua ispezionabile
- Lunghezza cavo elettrico 5 m
- Heavy-duty two wheeled trolley with handle
- Triplex pump with ceramic pistons and connecting rod system
- Brass pump head
- Automatic by-pass valve with pressure with pump head pressure discharge
- Remote control for total shut-down of high pressure washer
- Three-phase induction motor with thermal protector
- Flanged pressure unloader (VRZ)
- Pressure gauge
- Built-in detergent suction
- Adjustable detergent injector
- Built-in detergent tank capacity 3 l
- Inspectable water filter
- Electric cable length 5 m

Fornito con - Equipped with:

AL 13
Pistola 1/4" (M) M22x1,5
Trigger gun
(41046)



Tubo AP 10 m / HP Hose 10 m
Modelli senza RLW / Without RLW
SAE100 R1 armato / reinforced (1271960)



Lancia
Lance
(3600650)



Ugello / Wash nozzle
Bassa pressione / low pressure (3600400) - Nero / Black
Getto dritto / pencil jet SS 005 (3600720) - Rosso / Red
Getto ventaglio / fan jet SS 1505 (3600730) - Giallo / Yellow
Getto ventaglio / fan jet SS 2505 (3600740) - Verde / Green
Getto ventaglio / fan jet SS 4005 (3600750) - Bianco / White



RLW

Versione RLW a richiesta
RLW Version on request
15m



Gancio porta lancia
Lance holder



Serbatoio detergente integrato
Built-in detergent tank



Sistema di bloccaggio/sbloccaggio leva avvolgitubo
Hose reel lever lock/release system



(HRC)

Dati Tecnici / Technical Data

MOD	COD	MAX		l/h		kW	rpm	Hz	V	HP	kg
		bar	psi	l/h	gph						
1004 [◊]	25302	150	2200	900	238	5	1450	3~50	400	5,5	51,9
1004 RLW [◊]	25303	150	2200	900	238	5	1450	3~50	400	5,5	55,2

Temperatura massima acqua / Max inlet water temperature

60°C 140°F IPX5-S1 ◊ A richiesta / On request 230V 1450 rpm - 3~50 Hz