



78 Series 7850 · 7870



Acqua calda
Hot Water



Per uso professionale
For professional usage



Accessori professionali
Professional accessories

TSS[®]
Total Stop
SYSTEM

Caratteristiche Generali - General Features:

- Pompa a 3 pistoni in ceramica con sistema biella-manovella
- Testa pompa in ottone
- Valvola di by-pass automatica con azzeramento della pressione nella testa della pompa
- Motore elettrico trifase con protezione termica
- Sistema di arresto totale dell'idropulitrice a distanza
- Pressostato di sicurezza per spegnimento della caldaia in caso di mancanza acqua
- Caldaia verticale in acciaio inox, con sistema di raffreddamento bruciatore a chiocciola azionata da motore elettrico indipendente, doppia serpentina e fondo in cemento refrattario
- Scheda micropertite con segnalatore acustico
- Scheda di ritardo per spegnimento caldaia
- Regolazione pressione
- Serbatoio gasolio 15 l, con tappo di scarico
- Termostato
- Aspirazione detergente incorporata
- Serbatoio detergente 4/5 l incorporato
- Filtro acqua e filtro aspirazione gasolio
- Lunghezza cavo elettrico 5 m
- Triplex pump with ceramic pistons and connecting rod system
- Brass pump head
- Automatic by-pass valve with pump head pressure discharge
- Heavy-duty three-phase motor with thermal protector
- Remote control for total shut-down of high pressure cleaner
- With safety pressure switch to shut down the boiler in case of lack of water
- Stainless steel vertical boiler with coil burner cooling function driven by independent motor, double coil and refractory cement bottom
- Minor leak detector PCB with buzzer
- Heating boiler shut-down delay circuit
- Pressure adjustment built-in
- Fuel tank with drain plug (15 l)
- Thermostat
- Built-in detergent suction
- Built-in detergent tank capacity 4/5 l
- Water filter and fuel inlet filter
- Electric cable length 5 m



Fornito con - Equipped with:

MV951
Pistola 3/8"(F) · M22x1,5 con prolunga
Trigger gun with extension
(41089)



Tubo AP 10m armato
10m reinforced HP hose
DN 8 - Max 210°C (3160160)



Lancia
Lance
(40826)



Ugello 1/4 MEG
Wash nozzle
7850 (3083) - (1505)
7870 (3086) - (15045)



Caldaia in acciaio
Stainless steel boiler



Spie: tensione, gasolio, fiamma.
Termostato per regolazione temperatura acqua
Warning lights: power on, fuel, flame. Water temperature control thermostat



Mod. 7850
(HRC)



Mod. 7870
(HRR)

Dati Tecnici / Technical Data

MOD	COD	MAX		l/h		⚡		🌡️		⚖️				
		bar	psi	l/h	gph	kW	rpm	Hz	V	HP	°C	°C Max	Δt	kg
7850	25277	150	2200	900	238	5	1450	3~50	400	5,5	30	150	70	94
7870	25278	200	2900	900	238	7,4	1450	3~50	400	7,5	30	150	60	98

Temperatura massima acqua / Max inlet water temperature 60°C 140°F - IPX5-S1