


3-Port Non-vented



Counterbalance valves with pilot assist are meant to control an overrunning load. The check valve allows free flow from the directional valve (port 2) to the load (port 1) while a direct-acting, pilot-assisted relief valve controls flow from port 1 to port 2. Pilot assist at port 3 lowers the effective setting of the relief valve at a rate determined by the pilot ratio.

Other names for this valve include motion control valve and over-center valve.

### TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|   |                         |
|---|-------------------------|
| Cavity  | T-17A                   |
| Series  | 3                       |
| Capacity  | 240 L/min.              |
| Pilot Ratio   | 10:1                    |
| Maximum Recommended Load Pressure at Maximum Setting    | 270 bar                 |
| Maximum Setting   | 350 bar                 |
| Factory Pressure Settings Established at                | 30 cc/min.              |
| Maximum Valve Leakage at Reseat                         | 0,3 cc/min.             |
| Adjustment - No. of CCW Turns from Min. to Max. Setting | 3.75                    |
| Operating Characteristic                                | Standard                |
| Reseat  | >85% of setting         |
| Valve Hex Size  | 31,8 mm                 |
| Valve Installation Torque                               | 203 - 217 Nm            |
| Adjustment Screw Internal Hex Size                      | 4 mm                    |
| Locknut Hex Size  | 15 mm                   |
| Locknut Torque  | 9 - 10 Nm               |
| Seal kit - Cartridge                                    | Buna: 990017007         |
| Seal kit - Cartridge                                    | Polyurethane: 990017002 |
| Seal kit - Cartridge                                    | Viton: 990017006        |
| Model Weight  | 0.59 kg.                |

### CONFIGURATION

|                         |                          |   |
|-------------------------|--------------------------|---|
| L                       | Control                  | Standard Screw Adjustment   |
| K                       | Functional Setting Range | 1000 - 2500 psi w/25 psi Check (70 - 175 bar w/ 1,7 bar Check), 2000 psi (140 bar) Standard Setting |
| N                       | Seal Material            | Buna-N  |
| (none) Material/Coating |                          |   |

CONFIGURATION OPTIONS

Model Code Example: CBGHLKN

| CONTROL                          | (L) | FUNCTIONAL SETTING RANGE (K)   | SEAL MATERIAL | (N) | MATERIAL/COATING                |
|----------------------------------|-----|--|---------------|-----|---------------------------------|
| L Standard Screw Adjustment      |     | K 1000 - 2500 psi w/25 psi Check (70 - 175 bar w/ 1,7 bar Check), 2000 psi (140 bar) Standard Setting  | N Buna-N      |     | Standard Material/Coating       |
| C Tamper Resistant - Factory Set |     | C 2000 - 5000 psi w/4 psi Check (140 - 350 bar w/ 0,3 bar Check), 3000 psi (210 bar) Standard Setting  | V Viton       |     | /AP Stainless Steel, Passivated |
|                                  |     | D 1000 - 2500 psi w/4 psi Check (70 - 175 bar w/ 0,3 bar Check), 2000 psi (140 bar) Standard Setting   |               |     | /LH Mild Steel, Zinc-Nickel     |
|                                  |     | J 2000 - 5000 psi w/25 psi Check (140 - 350 bar w/ 1,7 bar Check), 3000 psi (210 bar) Standard Setting |               |     |                                 |

TECHNICAL FEATURES

- Counterbalance valves should be set at least 1.3 times the maximum load induced pressure.
- Turn adjustment clockwise to decrease setting and release load.
- Full clockwise setting is less than 200 psi (14 bar).
- Backpressure at port 2 adds to the effective relief setting at a ratio of 1 plus the pilot ratio times the backpressure.
- Reseat exceeds 85% of set pressure when the valve is standard set. Settings lower than the standard set pressure may result in lower reseat percentages.
- Sun counterbalance cartridges can be installed directly into a cavity machined in an actuator housing for added protection and improved stiffness in the circuit.
- Two check valve cracking pressures are available. Use the 25 psi (1,7 bar) check unless actuator cavitation is a concern.
- This valve has positive seals between all ports.
- All 3-port counterbalance, load control, and pilot-to-open check cartridges are physically interchangeable (i.e. same flow path, same cavity for a given frame size).
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES

