


drain connection ($P_{\text{drain}} < 0,5 \text{ bar}$)
(Always connect directly to the tank)

Symbol



Type for 4xφ11:
30MR...X568HF

Type	Displacement cm ³	Pressure Pmax, [bar]	Speed n [min ⁻¹]	Dimensions							
				A	B	Inlet			Outlet		
						E	F	d	E	F	d
				mm		mm	mm	mm	mm	mm	mm
30MR22.5X568H	22.5	200	500 ... 2500	57.6	119.7	φ40	φ19	M8-6H	φ40	φ19	M8-6H
30MR25X568H	25	200	500 ... 2500	58.3	121.1	φ40	φ19	M8-6H	φ40	φ19	M8-6H
30MR28X568H	28	200	500 ... 2500	60.2	124.7	φ40	φ19	M8-6H	φ40	φ19	M8-6H
30MR32X568H	32	200	500 ... 2500	66.5	137.3	φ51	φ27	M10-6H	φ51	φ27	M10-6H
30MR36X568H	36	200	500 ... 2300	68	140.5	φ51	φ27	M10-6H	φ51	φ27	M10-6H
30MR42X568H	42	200	500 ... 2300	70.8	146.1	φ51	φ27	M10-6H	φ51	φ27	M10-6H
30MR46X568H	46	200	500 ... 2100	72.7	149.8	φ51	φ27	M10-6H	φ51	φ27	M10-6H
30MR50X568H	50	185	500 ... 2100	74.5	153.4	φ51	φ27	M10-6H	φ51	φ27	M10-6H
30MR55X568H	55	165	500 ... 1750	76.7	157.9	φ51	φ27	M10-6H	φ51	φ27	M10-6H
30MR60X568H	60	150	500 ... 1750	78.7	162.4	φ51	φ27	M10-6H	φ51	φ27	M10-6H