



Vmax for calibrate pressure

Vmax for calibrate pressure

Rugosità delle superfici in Ra (um)

- Motor 1,5kW 3-ph 4-pole 230/400V 50/60Hz (~1450 rpm at 50Hz)
- Gear pump group 1 - 3,2cc/rev
- Universal A type PPC body, 1/4"BSPP P & T
- 10l cylindrical steel tank + 1/2"BSPP std filler & breather
- Relief valve 20-180bar
- 1 foot mounting support, 45mm height

03					
02					
01					
I.R.	MODIFICHE			FIR	DATA
Materiale	UNI	Salhydro Oy	Tratt. termico	UNI	
Dimensioni	UNI		Tratt. superficiale	UNI	
Stato	UNI		Durezza		
FIRMA	DATA		Denominazione		
Disegnato			Codice	I.R.	
Controllato			HN-PC400-15-33-10TS3	00	
Approvato			Documento riservato a termini di legge		
	Scala 1:4	Gruppo	<small>Shassi non quotati: Sn 0,2x45 °-Raggi R 0,4 max Tolleranze per dimensioni lineari, angolari e tolleranze geometriche prive di indicazioni di tolleranze specifiche: UNI ISO 2768-mk</small> FILETTATURE Madrevite Vite Metrica 6H 6g Gas H A ASA 2B 2A		
Meda (MD) - Italy					