


Switch - long lever

Coding: 104.1.F¹.6.27.S.W.F²

Operational characteristics	
Fluid	Filtered air. No lubrication needed, if applied it shall be continuous
Max. working pressure (bar)	10
Temperature °C	-5 ... +70
Flow rate at 6 bar with Δp=1 (Nl/min)	90
Orifice size (mm)	2.5
Working ports size	ø4 tube


TYPE	SWITCH POSITION (only for 5/3 ways)
22 = 2 ways, 2 positions	S 0 = 3 instable positions
32 = 3 ways, 2 positions	1 = 3 stable positions
52 = 5 ways, 2 positions	CONNECTION TYPE
53 = 5 ways, 3 positions	L = Lateral
FUNCTION 1 (only for 5/3 ways)	P = Rear
32 = Open centres	FUNCTION 2 (only for 2/2 or 3/2 ways)
33 = Pressured centres	A = Normally Open
	C = Normally Closed

2/2 - 3/2 - Lateral connections




Weight 65 g
Switch 2 positions stable

104.1.6.27.L.F²




2/2 - 3/2 - Rear connections




Weight 65 g
Switch 2 positions stable

104.1.6.27.P.F²




5/2 - Lateral connections




Weight 120 g
Switch 2 positions stable

104.52.6.27.L




5/2 - Rear connections




Weight 120 g
Switch 2 positions stable

104.52.6.27.P



5/3 - Lateral connections




Weight 120 g

104.53.F¹.6.27.S.L



5/3 - Rear connections



Weight 120 g

104.53.F¹.6.27.S.P

