


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS1414W
Parker Part No:	PR4534Q
OEM:	DIN Standard
OEM Part No:	DIN0160D05QV

Product Dimensions

A (mm)	80.0	(inch)	3.15
B (mm)	40.2	(inch)	1.58
D (mm)	80.0	(inch)	3.15
E (mm)	160.0	(inch)	6.30



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Mild steel tin plated
Bottom Endcap:	Mild steel tin plated
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	0.46 bar @ 160 l/min
Tested to ISO3968 @ 32 cSt	6.67 psi @ 35.20 gpm
Efficiency:	>Beta 200 @ 6 microns & greater >Beta 1000 @ 7 microns & greater
Minimum Collapse Pressure:	>20 bar
Tested to ISO2941	>290 psi
Dirt Holding Capacity acc. to ISO16889	39.8 gram @ 7 bar terminal pressure drop 39.8 gram @ 102 psi terminal pressure drop