6.3.2020 Scheda prodotto





Essiccatori a ciclo frigorifero

TDRY 9 V230/50/1 CE

Code: 4102002782 TDRY 9 V230/50/1 CE

Brand: FIAC

Category: Refrigeration dryers

Together with dust and oil vapours, compressed air also contains a certain amount of humidity, drawn from the external environment, which could cause the formation of condensate. Therefore, to ensure the correct operating efficiency of pneumatic equipment, the degree of relative humidity within the compressed air must be drastically reduced.

FIAC TDRY is a range of refrigeration dryers class 4 (ISO 8573-1) available with following components:

PDP indicator

The operation of the TDRY dryer is monitored by an electronic controller indicating all relevant information **Technical details:**

- refrigerant dryer status
- fan status
- dew point indicator

Alarm display:

- high / low dew point alarm
- fan probe failure (TDRY 12-77)
- maintenance warning

Control panel with free contact (on request):

- remote PDP alarm (TDRY 24-840)
- remote refrigerant high temperature (TDRY 24-840)
- remote fan probe failure (TDRY 24-77)

Intelligent capacitive condensate drain valve:

All dryer range is equipped with capacity condensate drain valve that using electronic sensors to discharge only condensate and without wasting the compressed air.

Benefits:

- avoid compressed air leaks
- energy saving
- no noise and environmental friendly

Standard features (TDRY 100-840)

Free contacts for:

- remote start/stop
- remote general alarm
- remote drain alarm

l /min	CFM	m3/h	mbar	BSP	Volt/Hz/ph	mm / in	kg / lb	m3
850	30	51	0.25	3 / 4" M	230 / 50 / 1 CE	350 x 493 x 450 / 13.8 x 19.4 x 17.7	25 / 55	0.078