


## PURISTUSMITTATAULUKKO R2T (2SN EN 853 / SAE 100 R2AT)




- Käyttölämpötila -40°-100°C
- Sisäputki öljynkestävää synteettistä kumia
- Kaksi ristiinkudottua teräskudosta

### PX (BXT2)



Tuotekoodi	Puristusmitta Ø (mm)	Tehdas- koodi	Työpaine (bar)	Mitat L x D (mm)
<b>PX-04</b>	<b>17,7</b>	BXT204	400	26x22
<b>PX-05</b>	<b>19,9</b>	BXT205	350	27,5x24
<b>PX-06</b>	<b>21,7</b>	BXT206	330	30x26
<b>PX-08</b>	<b>25,0</b>	BXT208	275	32,5x30
<b>PX-10</b>	<b>28,5</b>	BXT210	250	35x34
<b>PX-12</b>	<b>33,3</b>	BXT212	215	40x38
<b>PX-16</b>	<b>42,0</b>	BXT216	165	50x48
<b>PX-20</b>	<b>51,5</b>	BXT220	125	57x60
<b>PX-24</b>	<b>58,2</b>	BXT224	90	62x67
<b>PX-32</b>	<b>72,3</b>	BXT232	80	66x80

### PXV (B12T N)



Tuotekoodi	Puristusmitta Ø (mm)	Tehdas- koodi	Työpaine (bar)	Mitat L x D (mm)
<b>PXV-04</b>	<b>19,0</b>	B12T04N	400	30x23
<b>PXV-06</b>	<b>21,3</b>	B12T06N	330	32x26
<b>PXV-08</b>	<b>24,4</b>	B12T08N	275	34x29
<b>PXV-10</b>	<b>28,8</b>	B12T10N	250	37x33
<b>PXV-12</b>	<b>32,0</b>	B12T12N	215	42x37
<b>PXV-16</b>	<b>40,3</b>	B12T16N	165	51x46